

# ONYX® 8" Rotary, DC / IC Target, High Uniformity Magnetics

## US Specifications

Construction						
	Anode		304 Stainless Steel			
	Cathode Body		OFHC Copper			
	Insulator		Consult Factory			
Со	oling Requireme	nts				
	Flow Rate at Maximum Power		Consult Factory			
	Maximum Input Pressure, Open Drain		60 psi			
	Maximum Input Temperature		68 °F			
Din	nensions					
	A	Consult Factory	В—————————————————————————————————————			
	В	Consult Factory				

#### General

Magnetic Enhancement	Permanent (NdFeB) Encapsulated
Maximum Temperature	Consult Factory
Source to Substrate Distance	Consult Factory
Weight, Approximate Without Options	Consult Factory
Weight, Approximate Without Options	Consult Factory

# Maximum Sputtering Power \*

Cathode Voltage	Consult Factory
Direct Cooled Mode, DC	Consult Factory
Direct Cooled, Mode, RF	Consult Factory
Discharge Current	Consult Factory
Indirect Cooled Mode, DC	Consult Factory
Indirect Cooled Mode, RF	Consult Factory
Operating Pressure	Consult Factory

Mounting, S	Standard
-------------	----------

	Cathode Mounting	Flange		
	Power Connector, DC	Consult Factory		
	Power Connector, RF	Consult Factory		
	Water, Outer Dimension Tubing	Consult Factory		
P	Power Requirements			
	Drive	Consult Factory		
	Readout	Consult Factory		
Target				
	Cooling	Direct / Indirect		
	Diameter	Consult Factory		
	Form	Circular / Planar		
	Thickness	Consult Factory		

## Specifications Disclaimer

- All Angstrom Sciences NdFeB magnets are totally encapsulated and protected from degradation by water.
- · All sources are available in external configurations.
- \* Maximum power for cathode only, a target material's properties, such as, thermal and electrical conductivity may limit the maximum process power level.
- Some custom-engineered and specialty magnetrons may not meet standard specifications.
- · Specifications are subject to change without notice.
- Typical performance. Results may vary with process parameters such as pressure, flow rate, target material, and substrate rotation, etc.

Please contact us for specifications regarding your application.

Angstrom Sciences | Call +1-412-469-8466 | www.angstromsciences.com